LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Saw - Wet Tile Saw With Stand 250mm 1600W

Marque: DEWALT

Ref Product: wire:D24000S-QS

Ref Mcmining: DEWALTD24000S-QS

DESCRIPTION	
	- Stainless steel rail system is intergrated into the tile saw frame, ensuring accurate cuts - Cantilevering rail / cart system allows for 610 mm ripping capacity - Low weight allows one person to transport and set up saw - Plunge feature allows the user to make quick plunge cuts for electrical outlets together with an intergrated 45 / 22.5 degree feature for quick angle cuts - Dual water nozzles can be adjusted for optimal water placement on the blade in order to minimise over-spray and mist - Rear and side water attachments can be placed on the tile saw to catch overspray - keeping the water in the pan - Removeable cutting cart for easy cleaning of tile saw - Edge guide with two positions (90 & 45 degree) allows easy line up of corner cuts - Integrated portable residual current device (PRCD) circuit breaker for increased user protection - STANDARD - D240001 leg stand - DT3734 cutting disc - Extention table - Side and rear water collector - Hex key
SPECIFICATIONS	
	- Power Input: 1600 Watts - Wheel Diameter: 250 mm - No Load Speed: 4200 rpm - Depth of cut: 95 mm - Max. Crosscut Capacity at 90º: 610 mm - Max. Crosscut Capacity at 45º: 450 mm - Width: 690 mm - Length: 860 mm - Weight: 32 kg - Bore size: 25.4 mm
BRAND	**DEWALT**