LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Salvage drum - Poly-Overpack® 65

Marque: ENPAC

Ref Product: wire:1065-YE

Ref Mcmining: EN1065-YE

Description	
Our Poly-Overpack® 65 meets Group 1 packaging standards and salvage drum regulations. Unlike competing overpacks, Our Poly-Overpack® 65 safely contains a wide range of hazardous materials including: acids, corrosives and damaged parts—in 30-gallon drums. - Tight, secure and leak-free container closing is simple: place any long object (like a wooden two-by-four) in the handy lid slots, and turn to screw the lid down tightly. - Meets performance-oriented packaging requirements of U.S. DOT and UN regulations. - Twist-down lid for safe closure. - Closed cell gasket in lid seals closure. - Castellations in lid allow for easy closing with pole or wooden 2x4” - Double wall lid gives added strength. - Molded area allows or easy gripping and lifting by material handling equipment. - Ribbed design provides extra strength. - 100% UV-protected polyethylene provides protection over a wide range of chemicals. Available in up to 100% recycled material, ECO-Efficient edition	
Specifications	
Top Diameter External:	27.75 in. / 70 cm.
Top Diameter Internal:	26.75 in. / 68 cm.
Bottom Diameter External:	23 in. / 58 cm.
Bottom Diameter Internal:	22 in. / 56 cm.
Height Internal:	37.5 in. / 95 cm.
Height External:	34.25 in. / 87 cm.
Weight:	47 lbs. / 21 kg.
Load Capacity:	440 lbs. / 200 kg.
Spill Capacity:	65 gal. / 246 L
Regulations:	**UN 1H2/X200/S** **DOT 40 CFR 264.175 - EPA SPCC, NPDES**