Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Laser leveler - Self Leveling Cross Line Laser 15m Visibility

Marque: DEWALT

Ref Product: wire:DW088K

Ref Mcmining: DEWALTDW088KTRI-XJ

Features	
Self-levelling cross line laser is accurate to Â±0.3 mm/m in levelling applications - Self-Levelling up to 4 degrees surface angle with automatic out of level indication, marks a levelled line in seconds - 2 button operation and low battery indication for ease of use - Built in magnetic pivot bracket mounts easily on metal surfaces - Overmolded housing and thick glass protects the tool and helps maintain calibration under jobsite conditions - Includes 3 x AA batteries for 40 plus hours runtime - Kit box protects unit and helps maintain calibration when stored in gang box - Works with DE0892 detector up to the distance of 50 metres - Comes with "Floor to Ceiling" 1/4" thread, up to 3.4m height pole - 360 degree horizontal rotation with no height change - Easy to actuate locking mechanism - Reinforced fixing arm platform, locking mechanism and sections connecting material - STANDARD - 3 x AA size alkaline batteries - Wall mount bracket - Heavy duty carrying case - DE0882 Laser Pole	
Specifications	
Power Supply:	4.5V - 3x AA
Self-Leveling Range	
Indoor Visibility Range	
Laser Class	
Tool Weight	
Shipping Weight	
Type de laser :	2, <1mW
Accuracy :	+/-0.3 mm/m
Number of beams:	2
Direction of beams vertical/level	
Indoor visibility range:	10 m
Self-levelling range:	+/-4 Âº
Tripod connection:	1.4"
Weight (incl. battery):	0.46 g
Width:	61 mm
Length:	112 mm
Height:	113 mm
Chuck:	Capacity
Power Input	
Power:	Output
Max.:	Torque

No Load Speed	
Max. Drilling Capacity [Wood] :	
Max. Drilling Capacity [Steel] :	
Spindle Thread :	
Weight :	
Hand/Arm Vibration - Metal :	
Uncertainty K 1 (Vibration) :	
Sound Pressure :	
Uncertainty K 1 (Sound) :	
Accoustic Pressure :	
Uncertainty K 2 (Sound) :	