LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Hammer, sledge - 15,00lbs FG0073A AlBz

Marque: AMPCO

Ref Product: wire:FG0073A

Ref Mcmining: PRFG0073A-AM

Description

Ampco non-sparking products are intended for use in areas where a high risk of fire or explosion exists,as in the presence of flammable gases or liquids.Non-magnetic Ampco tools are recommended in military applications,Â mine clearance operations and in the medical field, for MRI and other scanning equipment or equipment using large magnets. Outstanding corrosion resistance also make Ampco tools the professional's choice in the most demanding and aggressive environments,on land or water.

The striking face is designed for general blacksmith work in striking unhardened metal. The peins are used for shaping (fullering) and bending unhardened metal.

Never use a sledge to strike a hammer, sledge or maul. Never use a sledge with loose or damaged handle.

Certifications

- **ISO9001**

AMPCO SAFETY TOOLS Aluminum Bronze (AlBz) alloy helps fulfill the recommendation in:

- **European ATEX directive** for working in Zones 0 and/or 20 of all explosion groups.

- **BAM (FEDERAL INSTITUTE FOR MATERIALS RESEARCH AND TESTING, Berlin Germany) Standard operating procedure "QMH-NEG-005"** "StAA zur Schlagfunkenprüfung von Werkstoffpaarungen" dated 2012-03-01 : non-sparking tools made of these materials are appropriate for use in potentially explosive atmospheres of zone 0, 1, 2 and 20, 21, 22 according to directive **1999/92/EC** of all explosion groups according to **IEC 60079-20-1:2010**.

- **EN 1127-1 and EN 13463-1**

Specification

REF	H lbs	H g	l mm	g	
FG0073A	15	6800	840	7300	