Mc MINING GROUPE PICHORI Quality First

LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet



Miniature circuit breaker (MCB), Easy9, 1P+N, 25A, C curve, 6000A

Marque: SCHNEIDER ELECTRIC

Ref Product: wire:SCEZ9P35625

Ref Mcmining: SCEZ9P35625

DESCRIPTION	
Miniature circuit breaker (MCB), Easy9, 1P+N, 25A, C curve, 6000A (IEC/EN 60898-1)	
EZ9P35625	
It is a 1P+N circuit breaker with 1 protected pole	
In rated current	25A
tripping curve.	C
Icn rated short circuit breaking capacity	up to 6000A at 230VAC conforming to IEC 60898-1 standard.
Standard	**compliant with IEC 60898-1 standard.**
protection against	short circuit
protection of cable against	overloads.
fault tripping indication on the front panel by the position of the handle	(O-I engraved).
dedicated for	residential and small commercial buildings.
electrical endurance	up to 4000 cycles
mechanical endurance	going up to 10000 cycles.
Ue operational voltage	230VAC.
Uimp rated impulse withstand voltage	4kV.
operating frequency	50Hz.
can be mounted on	DIN rail for modular installation.
width	2 pitches of 9mm.
dimensions	(W) 18mm x (H) 81mm x (D) 78mm.
degree of protection	IP20 According to IEC 60529 standard / IP40 in enclosure.
operating temperature	-25°C to 60°C.
storage temperature	-40°C to 85°C.