LEADER IN INDUSTRIAL TOOLS & EQUIPMENT

Technical sheet

Image not found or type unknown	**SabreLite™ 2000 Flashlight** Marque: PELICAN Ref Product: wire:2000C Ref Mcmining: PELICAN2000C

Specification	This powerful flashlight was designed with one thing in mind: - SAFETY. It carries more approvals than any other flashlight on the market today, making it safe for any hazardous environment or condition. - The SabreLite is o-ring sealed with a twist-on shroud and comes with a polarity battery guard tray that safeguards against dangerous "outgassing" of hydrogen from an accidentally reversed cell. - It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures. - Unlike ordinary flashlights that produce a yellow beam, the SabreLite\'s incredibly bright Xenon lamp produces a powerful collimated white beam. - Pelican\'s SabreLite is the leader in quality and performance. Light source: Xe no n Batteries: 2 AAA Alkaline (Includ e d) Charge time: N/A Voltage: 3 Length: 4.0 9 " (10 .4 cm) Weigth w batteries: 1.6 o z. (0 .0 5 kg) Weigth w/o batteries: 0 .75 o z. (0 .0 2 kg) Light output: 11 LUMENS Runtime: 1h 30 m Beam distance: 45m Peak beam intensity: 571cd Waterproof and submersible: 1m **MADE IN USA**
Configurations:	2000 : SabreLite™ 2000 Flashlight (Carded) 2000PL : SabreLite™ 2000 Flashlight w/ Photoluminescent Shroud (Carded)
Certification:	**CSA:** Class I, Div. 2; Gp ABCD, T3C; Class ll; Div. 2; Gp G. **FM:** Class I, ll, Div. 2; Gp. ABCD/G , T3C. **UL :** Listed 4S67/E184884 Class I, Div. 1; Gp.C, D / Class l; Zone 1; Gp.llA; llB; T3C **MSHA:** 10C-629-2 **IECex :** IEC Ex TSA 06.0021X Ex ib e IIC T4 IP67
Color:	Black/yellow
Packing	Minimum Pack 6 ea. Packaged Weight: 6.8 oz
Color	**Ref Mc Mining**
Black	**PELICAN2000C-BLACK**
Yellow	**PELICAN2000C**